HI97701

Free Chlorine Portable Photometer

Advanced LED optical system

- Innovative optical design that utilizes a reference detector and focusing lens to eliminate errors from changes in the light source and from imperfections in the glass cuvette.
- LEDs have a much higher luminous efficiency, providing more light while using less power. They also produce little heat, which could otherwise affect electronic stability.

CAL Check™

 Validate instrument performance at any time using CAL Check cuvettes made with NIST traceable standards. The CAL Check screen guides the user step-by-step through the validation process and user calibration.

• On-screen tutorial mode with animations

- Guides users step-by-step through the measurement process
- Waterproof and floating IP67 case
- Unit of measure is displayed along with reading
- Built-in timer
 - Built-in reaction timer that ensures consistency between tests.
- Error messages on display
 - Alerts to problems including no cap, high zero, and standard too low
- GLP data
 - Displays the last calibration date.
- Auto logging
- · Battery status indicator
- · Auto-shut off



y @25°C (77°F) burce ss filter dth ss filter ngth accuracy	0.00 to 5.00 mg/L (as Cl ₂) 0.01 mg/L ±0.03 mg/L ±3% of reading at 25 °C adaptation of US EPA method 330.5, DPD Colorimetric method light emitting diode 525 nm 8 nm ±1.0 nm
y @25°C (77°F) ource ss filter dth ss filter ngth accuracy	±0.03 mg/L ±3% of reading at 25 °C adaptation of US EPA method 330.5, DPD Colorimetric method light emitting diode 525 nm 8 nm
ource ss filter ss filter dth ss filter ngth accuracy	adaptation of US EPA method 330.5, DPD Colorimetric method light emitting diode 525 nm 8 nm
ss filter ss filter dth ss filter ngth accuracy	light emitting diode 525 nm 8 nm
ss filter ss filter dth ss filter ngth accuracy	525 nm 8 nm
ss filter dth ss filter ngth accuracy	8 nm
dth ss filter ngth accuracy	
ngth accuracy	±1.0 nm
hactar	
Light Detector Cuvette type	silicon photocell
	round 24.6 mm diameter (22 mm inside)
Auto-off Additional	50 readings
	128 x 64 pixel B/W LCD with backlight
	after 15 minutes of inactivity (30 minutes before a READ measurement)
type/Life	alkaline 1.5 V AA (3) / > 800 measurements (without backlight)
Environment Dimensions Weight	0 to 50°C (32 to 122°F); 0 to 100% RH, non-serviceable
	142.5 x 102.5 x 50.5 mm (5.6 x 4.0 x 2.0")
	380 g (13.4 oz.)
	type/Life ment

Reagents and Standards

Ordering

Information

HI97701

HI97701-11 CAL Check standard cuvettes for free and total chlorine

HI97701C includes photometer, CAL Check standards, sample cuvettes (2), sample caps (2),

plastic stoppers (2), 1.5V AA batteries (3), cuvette wiping cloth, scissors, CAL Check standard certificate, instrument quality certificate, instruction manual, and HI7101412 rigid carrying case.

HI93701-01 free chlorine powder reagent (100 tests)
HI93701-03 free chlorine powder reagent (300 tests)
HI93701-F free chlorine liquid reagent (300 tests)

